Thread BSP BSPT NPT Camlock Quick Couplings With Stainless Steel 304 316

Basic Information

Place of Origin: CHINABrand Name: DEYE

Certification: ISO9001:2015 PED

Model Number: DY-QC-02Minimum Order Quantity: 10PCS

• Price: USD2-USD25 each

Packaging Details: carton box+ ply wooden cases or carton+

Pallets

• Delivery Time: 20 days for usual order, 7 days for stocked

items

• Payment Terms: T/T, L/C, D/P

• Supply Ability: 1000pcs one month



Product Specification

Highlight: NPT Camlock Quick Couplings,
PSDT Camlock Quick Couplings.

BSPT Camlock Quick Couplings, BSP 4 inch camlock fittings

Product Description

Thread BSP BSPT NPT Camlock Quick Couplings With Stainless Steel 304 316

Camlock couplings which are also called camlock hose fittings, a hose cam lock, cam fittings, a cam coupling and cam lock hose connectors. Camlock couplings facilitate the transfer of commodities between two hoses or pipes. They are simple to connect and disconnect, requiring no tools

Product Information/Product Description/Basis Information/Specification

Name	Camlock Quick Coupling	
Material	stainless steel ANSI 304,316,304L,316, Aluminum, Brass, PP	
Size	1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8" 10" 12"	
Thread	Thread BSP, BSPT, NPT, DIN259/2999 EN ISO228-1	
Туре	A, B, C, D, E, F, DC, DP (A, B, D, F with thread, B, C, D, DC with handles)	
	Type "A", has a male grooved adapter and a female pipe thread (BSP or NPT thread) of the same size	
	Type "B", has a female camlock end and a male pipe thread of the same size	
	Type "C", has a female camlock on one end and a male hose tail on the other	
	Type "D", has a female camlock end and a female pipe thread of the same size	
	Type "E", has a male camlock on one end and a male hose tail on the other	
	Type "F", has a male grooved adaptor and a male pipe thread of the same size	
Gaskets	NBR, EPDM, Viton, PTFE gasket are all available	
Cam levers	We use stainless steel cam levers	
Pressure	3/4"-2" 250PSI (17.6bar),3"-4" 200PS I(14.8bar)	
	2 1/2" 225PSI (15.8bar),6" 150PSI (10.5bar)	
Technology	Investment casting. Precision casting, NC machine	
Packing	pcs/polybag, polybag/carton, cartons/pallet or according to your requirement	
Certificate	ISO9001:2015	
Process	CNC machine, Testing equipment	
	,	

Features /Advantages:

- 1. Simple structure, convenient operation, quick connect and open it.
- 2.compact size, light weight, good sealing and interchangeability.
- 3. Adapt to all kinds of working conditions, widely used in liquid, powder and other medium.
- 4. Joint connected with taper pipe threads, outside taper pipe threads, intubation connection, flange connection, etc.
- 5. Cam & groove couplings are easy to operate. Camlock consists of two parts male adapter and female coupler. You just need insert the adapter into the coupler until contact is made with the gasket. Then press down the cam arms simultaneously to produce a uniform gasket compression. During the process of installation, no tools are required and hand pressure is enough. Hence, camlock fittings not only save your time but also the tools and human power.
- 6. Cam & groove couplings are equipped with PVC suction hoses, lay flat discharge hoses and other low-pressure hoses. It can simplify the operation and save working time greatly. However, cam locks are not suitable for any kind of hose. It is forbidden to be used in compressed air or gas or high-pressure applications.

Types of the cam & groove couplings

Type A	Type B
Male Adapter X Female	Female Coupler x Male
DEY	DEVE 3
Ty pe C	Type D
Female Coupler X hose Shank	Female Coupler x Female
DEYE	9.55 (1-i)
Type E	Type F
Male Coupler X Hose Shank	Male Adapter xMale
SYE	
Type DC	Type DP
Dust Cap	Dust Plug
DEYIP OF 17-BE S 116	DEYE

Application and usage

Quick release coupling for low-pressure systems, Suitable for Construction; Fire hydrant; Garden; Farming

Our Service

- 1. Technical support
- 2. Raw Material Quality control.
- 3. Inspection during the production time.
- 4. Final Test includes Surface, Dimension, PT Test, RT test, ultrasonic Test
- 5. Test Report each shipment
- 4. Flexible Delivery terms. EXW FOB CIF CFR DDP DDU
- 5. Flexible payment Ways: LC. TT. DP
- 6. Customized Package includes Logo. Cases Dimension.
- 7. 18 months quality Guarantee time.
- 9. Free replacement by air if any error founded
- 10. 24 hours to Feedback your questions





